

**Product Data Sheet**

**Application:** Pitched Roofs

# SPACESAVER



## Thermal Insulation for Pitched Roof Joist Applications

Spacesaver is a glass mineral wool roll which is pre-perforated to fit between common joist spacing at ceiling level. It is supplied in longer-length rolls to help increase the speed of installation and ensure more efficient delivery and storage. Other products within the range include Spacesaver Lite, Spacesaver Ready-Cut and Spacesaver Plus.

Spacesaver can also be considered for use between the joists in suspended timber ground floors and flat roofs.

## Features and Benefits



### Thermal Performance

Thermal conductivity of 0.044 W/m.K. Helps to reduce heat loss within the building envelope and decrease energy costs.



### Easy to Install

Supplied in longer-roll lengths for quick and easy installation, maximising on-site efficiency. The rolls are pre-perforated (3 x 386 and 2 x 580mm widths) to fit common joist spacing, or can be used full width for quick coverage.



### Sustainability

Achieves a BRE Green Guide rating of A+ which can assist in demonstrating environmental performance in your BREEAM assessments. Manufactured from up to 75% recycled glass on a plant that uses 100% renewable electricity. For further details, see the Environmental section below or visit [insulation-uk.com/CSR](https://insulation-uk.com/CSR)



### Fire Classification

Achieves a Euroclass A1 Reaction to Fire classification, according to EN 13501-1.

# Key Considerations

When using ISOVER Spacesaver, you need to satisfy yourself that use of the product meets all relevant national Building Regulations and guidance as well as local, national and other applicable standards relevant for your construction or application, including requirements in relation to fire and applicable height restrictions.

Please refer to the following product documents:

- Declaration of Performance - available at [insulation-uk.com/dop](https://insulation-uk.com/dop)
- Safe Use Instruction Sheet - available at [insulation-uk.com/healthandsafety](https://insulation-uk.com/healthandsafety)

# Product Specification

Product code	Thickness (mm)	Length (m)	Width* (m)	Roll area (m <sup>2</sup> )	Rolls per pallet	Pallet area (m <sup>2</sup> )	λD Declared thermal conductivity (W/m.K)	RD Declared thermal resistance (m <sup>2</sup> .K/W)
5200854520	100	12.18	1.16	14.13	24	339.09	0.044	2.25
5200854529	150	8.05	1.16	9.34	24	224.11	0.044	3.40
5200854549	170	7.03	1.16	8.15	24	195.72	0.044	3.85
5200840154	200	5.20	1.16	6.03	24	144.77	0.044	4.50

\*Pre-perforated to 3 x 386mm and 2 x 580mm widths

# Characteristics

**Thermal** Declared thermal conductivity of 0.044 W/m.K under EN 13162: Thermal insulation products for buildings. Factory made mineral wool (MW) products.

**Fire** Euroclass A1 Reaction to Fire classification according to EN 13501-1.

**Environmental** All ISOVER products are manufactured under Environmental Management System - ISO 14001:2015. Achieves an A+ Green Guide rating for glass mineral wool insulation ref 815320005 that can assist in demonstrating the environmental performance within BREEAM assessments.

**Recycled Content** Manufactured from up to 75% recycled glass.

**Certification** UKCA Marked to BS EN 13162. CE marked to EN 13162. Designation code: MW-EN 13162-T1.

**Handling, Storage, Health and Safety** Information regarding storage, installation and handling of ISOVER products and health & safety information can be found at [insulation-uk.com/healthandsafety](https://insulation-uk.com/healthandsafety). Achieves a Eurofins Gold product status for indoor air quality (certificate available at [insulation-uk.com/Eurofins](https://insulation-uk.com/Eurofins)). EUCEB certified, demonstrating our mineral wool fibre products conform with Note Q of Regulation (EC) No 1272/2008 (to download the certification, please visit [insulation-uk.com/accreditations](https://insulation-uk.com/accreditations)).



**ISOVER**

White House Industrial Estate,  
Runcorn, Cheshire, WA7 3DP

**Customer Service -  
Order Placement and Enquiries**

Tel: 01473 820820

Email: [iukcustomerservice@saint-gobain.com](mailto:iukcustomerservice@saint-gobain.com)

**Technical Support Centre**

Tel: 01473 820850

Email: [technicalsupport@saint-gobain.com](mailto:technicalsupport@saint-gobain.com)

**[insulation-uk.com](http://insulation-uk.com)**

Published date: 18 Jul 2023

Document reference: 001-441

ISOVER reserves the right to amend or revise product specification without notice. The information in this publication is correct at the time of publication. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work.

For an up-to-date library of product information, users should visit the website at [insulation-uk.com](http://insulation-uk.com)

Saint-Gobain ISOVER UK Registered in England. Company Number 10442670.

Registered Offices: Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU.